









REF.	FA 40 905 20
CE	EN 358:1999, ISO 9150 :1988, ISO 15025:2002
LG. (MIN. / MAX.)	1.2 m / 2.0 m
MAT.	 35 mm ARAMID
	 STEEL
MAT. 	 STEEL
	0.57 KG

MAT.



Matière Matière connecteurs
Material Material of connectors
Material Material de los conectores
Materia Materie conettori
Material Material der Verbinder

MAT.



Matière Matière boucle de réglage / coulisseau
Material Material of adjustment buckle / rope grab
Material Material de hebilla de ajuste / corredera
Materia Materia fibbia di regolazione / anticaduta scorrevole
Material Material der Einstellschnalle/des Gleitelements



Sangle pouvant résister jusqu'à des températures maximales de 371°C

Strap that can withstand temperatures up to 371 °C

Correa que puede resistir temperaturas máximas de hasta 371 °C

Cinghie possono resistere alle temperature di massimo 371°C

Gurt hitzeresistent bis maximal 371°C



Sangle pouvant résister à des projections de métal en fusion

Strap that can withstand splashes of molten metal

Correa que puede resistir proyecciones de metal en fusión

Cinghie possono resistere alle proiezioni di metallo in fusione

Gurt beständig gegen Spritzer von Schmelzmetall



HS CODE
63079098
CARTON SIZE / PCS.
60 x 40 x 36 cm / 25
AET N°2777/10351-02/E03-01
Satra Technology Europe Ltd., N° 2777, Bracetown Business Park, Clonee, Dublin, D15YN2P, Ireland
MODULE D F114/14003.02
SGS Fimko Oy, N°0598 Takomotie 8, 00380 HELSINKI, Finland
AET (UKCA) N°AB0321/16030-01/E01-01
Satra Technology Centre, N°0321 Wyndham Way, Telford Way, Kettering Northamptonshire, NN16 8SD, United Kingdom
MODULE D 11 IN14/14003
SGS United Kingdom Ltd., N°0120 Unit 202B, Worle Parkway, Weston-super-Mare, BS22 6WA, United Kingdom