

## DIELECTRIC ENERGY ABSORBING WEBBING LANYARD




Energy absorbing lanyard designed to protect the operators working in an environment with potential electrical hazards.

- Energy absorber in 44 mm wide webbing, which reduces the impact of fall to less than 6kN. Energy absorber equipped with a fall indicator. Has a black protective sleeve for increased longevity and UV-resistance.
- 30 mm wide polyester webbing.

### Connectors:

One textile loop at one end for attachment to the dorsal D-ring of the harness, and one dielectric rebar hook FA 50 222 55 at the other end.



**Compliance :** EN355 : 2002.

### Material of components:

Strap: Polyester.

Absorber: Polyester and Polyamide.

Connector: Steel with a polymer composite that can withstand a maximal voltage of 14kV.

<b>Length:</b>	<b>CE</b>	<b>Weight:</b>
1.80 m		1.06 kg

### KRATOS SAFETY

689 Chemin du Buclay  
38540 Heyrieux – FRANCE

Tel. : +33 (0)4 72 48 78 27

Fax : +33 (0)4 72 48 58 32

[www.kratossafety.com](http://www.kratossafety.com) / [info@kratossafety.com](mailto:info@kratossafety.com)

### HS CODE

6307 90 98

### CARTON SIZE / PIECES

80 x 40 x 24 cm / 10

AET N°4303 I6 E1

### Satra Technology Centre, N°0321

Wyndham Way, Telford Way, Kettering  
Northamptonshire, NN16 8SD, United Kingdom

### ARTICLE 11 GB07/73551

### SGS United Kingdom Ltd., N°0120

Unit 202B, Worle Parkway,  
Weston-super-Mare, BS22 6WA, United Kingdom