



FA 70 005 00



FA 70 021 00



FA 50 302 22B (x 4)

FA 70 010 99 (30) +  
FA 50 302 22BFA 60 005 00  
(x 2)

FA 90 106 00

This simple and light self-evacuation kit is designed to be used from an identified workstation at height, where a fall arrest harness may not be required. This system allows the evacuation of the user downwards.

### This kit is composed of:

- A rescue triangle **FA 70 005 00** with dorsal D-Ring for the guiding of the evacuation and shoulder straps made of elastic webbing,
- A descender made up of Aluminium alloy **FA 70 021 00** with self-braking system and safe locking eye, conform to EN 341,
- 4 Keylock Triple Action-locking karabiners **FA 50 302 22B**, conform to EN 362,
- A semi-static rope, length 30 m **FA 70 010 99 (30)**, conform to EN 1891, with 1 Keylock karabiner **FA 50 302 22B**,
- 2 anchorage webbing slings **FA 60 005 15**, length 1,50 m, conform to EN 795,
- A cylindrical PVC transport bag **FA 90 106 00**.

*This kit is also available in a 20 m version (FA 70 025 20) and in a 50 m version (FA 70 025 50).*

	<b>CE</b>	Weight :

### KRATOS SAFETY

689 Chemin du Buclay  
38540 Heyrieux – FRANCE

Tel. : +33 (0)4 72 48 78 27  
Fax. : +33 (0)4 72 48 58 32

[www.kratossafety.com](http://www.kratossafety.com) / [info@kratossafety.com](mailto:info@kratossafety.com)

### ARTICLE 11 GB07/73551

**SGS United Kingdom Ltd., N°0120**

Unit 202B, Worle Parkway,  
Weston-super-Mare, BS22 6WA, United Kingdom