



TECHNICAL SHEET FA 40 904 40

WORK POSITIONING TWISTED ROPE LANYARD WITH GRIP ADJUSTER, MAX. LG. 4 MTRS



Made up of 14mm diam. polyamide twisted rope.

Abrasion resistant thimble to protect the loops from being damaged by contact with metal parts.

Spliced end is protected with a strong transparent covering sleeve.

Colored tracer strand losing color to show that the lanyard is unfit for use.

Grip adjuster for an easy "one-hand" length adjustment.

Length of the protective sleeve: 1.5 mtr.

Connectors: 1 screw-locking karabiner, opening 18 mm, ref. FA 50 101 17 and 1 snap hook, opening 17 mm, FA 50 202 17.

Breaking strength: 15 kN.

Compliance: EN358:1999.

Materials:

Lanyard: Polyamide

Protective sleeve: Polyester

Connectors: Steel

Grip Adjuster: Stainless steel

Max. length:

4 mtrs



Weight:

1.50 kg

KRATOS SAFETY

689 Chemin du Buclay
38540 Heyrieux – FRANCE

Tel. : +33 (0)4 72 48 78 27

Fax. : +33 (0)4 72 48 58 32

www.kratossafety.com / info@kratossafety.com

HS CODE

5609 00 90

DIMENSIONS CARTON / UC

80 x 40 x 24 cm / 10

AET N°4016 Issue 3 Extension 4

Satra Technology Centre, N°0321
Wyndham Way, Telford Way, Kettering
Northamptonshire, NN16 8SD, United Kingdom

ARTICLE 11 GB07/73551

SGS United Kingdom Ltd., N°0120
Unit 202B, Worle Parkway,
Weston-super-Mare, BS22 6WA, United Kingdom