Spasciani
YOUR SAFETY MAKER

FILTER
Model: 201 A2B2
P/N 123200000

Gas filter with standard thread connector to **EN 148-1** for organic vapours having boiling point higher than 65°C and inorganic gases and vapours.
The filter can be used with masks type **TR 82, TR 2002 CL2** and **TR 2002 CL3**, halfmasks **ST 85** or equivalent, provided that they are fitted with EN 148-1 connector.

TECHNICAL DATA
Inhalation resistance
at 30 l/min: 1.1 mbar
at 95 l/min: 4.5 mbar

Duration at gases

Filter type	Class	Testing Gas	Testing Concentration (PPM)	Testing Flow (l/min)	Testing HR (%)	Breakthrough concentration (PPM)	Duration Required (min)	Duration Tested (min)
A	2	C_6H_{12}	5000	30	70	10	35	>40
B	2	Cl_2	5000	30	70	0.5	20	>25
		H_2S	5000	30	70	10	40	>50
		HCN	5000	30	70	10	25	34

Limitations for use
Do not use in areas where the oxygen concentration is lower than 17% in volume nor in presence of gases different from those clearly indicated, dusts, fumes and mists.

CLASSIFICATION
Filter complying with Directive **89/686/EEC (PPE)**
Gas Filter, class 2, to **EN 14387:2004 + A1:2008.**
Label colour code: brown, grey.

YOUR SAFETY MAKER

FILTER
Model: 201 A2B2
P/N 123200000

MARKING
CE

MATERIALS
Housing: polypropylene
Filter Media: activated carbon

STORAGE
Store at temperatures between -20 and +50 °C and RH <80%

WEIGHT
225 g (7.9 oz) approximately

DIMENSIONS/PACKING
The filter is sold in 4 piece boxes with dimensions 220 x 220 x 90 mm

SHELF LIFE
Filters duly stored and in their original packaging will last five years from production. The expiry date is stamped onto the filter label and its packaging.