







<b>HS CODE</b>
56090090
<b>CARTON SIZE / PCS.</b>
60 x 40 x 36 cm / 25
<b>AET N° 2777/10963-01/E10-01</b>
<b>Satra Technology Europe Ltd., N° 2777,</b> Bracetown Business Park, Clonee, Dublin, D15YN2P, Ireland
<b>MODULE D FI14/14003.02</b>
<b>SGS Fimko Oy, N°0598</b> Takomotie 8, 00380 HELSINKI, Finland

REF.	FA 30 500 15	FA 30 500 20
<b>LG.</b>  <b>KG</b>	1.5 m (connector included)	1.8 m (connector included)
	-----	
	Max. 100 KG	
<b>CE</b>	EN 355:2002	
<b>MAT.</b>	 PA 11 mm Polyamide	
	35 mm	
	---	
	<b>NO</b>	
	0.39 KG	0.40 KG



**Largeur de l'absorbeur d'énergie**  
 Width of the energy absorber  
**Ancho del absorbedor de energía**  
 Larghezza del assorbitore di energia  
**Breite des Falldämpfers**



**Longueur** Poids maxi utilisateur  
**Length** Max. user weight  
**Longitud** Peso máximo del usuario  
**Lunghezza** Peso Max. dell'utente  
**Länge** Höchstgewicht des Benutzers



**Matière connecteur haut / connecteur bas**  
 Material of top connector / bottom connector  
**Material conector alto / conector bajo**  
 Materiale connettore alto / connettore basso  
**Material oberes / unteres Verbindungselement**



**Ouverture**  
 Gate opening  
**Apertura**  
 Apertura  
**Öffnung**



**Homologué pour le travail à proximité d'arêtes vives**  
 Approved for work near sharp edges  
**Homologado para trabajo cerca de aristas vivas**  
 Omologato per lavoro in prossimità di spigoli vivi  
**Zugelassen für Arbeiten in der Nähe scharfer Kanten**