



IRE FREE


HS CODE
56090090
CARTON SIZE / PCS.
60 x 40 x 24 cm / 12
AET N°2777/10363-02/E06-01
Satra Technology Europe Ltd., N° 2777, Bracetown Business Park, Clonee, Dublin, D15YN2P, Ireland
MODULE D FI14/14003.02
SGS Fimko Oy, N°0598 Takomotie 8, 00380 HELSINKI, Finland

REF.	FA 30 305 10 FA 30 305 15 FA 30 305 20
LG. 	1.0 m 1.5 m 2.0 m
CE	EN 355:2002, ISO 9150 :1988, ISO 15025:2016
MAT.	: 45mm ARAMID
	45 mm
	 FA 50 202 17 / FA 50 207 55
	NO
	1.10 KG 1.15 KG 1.19 KG



Largeur de l'absorbeur d'énergie
Width of the energy absorber
Ancho del absorbedor de energía
Larghezza del assorbitore di energia
Breite des Falldämpfers



Matière connecteur haut / connecteur bas
Material of top connector / bottom connector
Material conector alto / conector bajo
Materiale connettore alto / connettore basso
Material oberes / unteres Verbindungselement



Ouverture
Gate opening
Apertura
Apertura
Öffnung



Longueur Poids maxi utilisateur
Length Max. user weight
Longitud Peso máximo del usuario
Lunghezza Peso Max. dell'utente
Länge Höchstgewicht des Benutzers



Homologué pour le travail à proximité d'arêtes vives
Approved for work near sharp edges
Homologado para trabajo cerca de aristas vivas
Omologato per lavoro in prossimità di spigoli vivi
Zugelassen für Arbeiten in der Nähe scharfer Kanten



Sangle pouvant résister jusqu'à des températures maximales de 371°C
Strap that can withstand temperatures up to 371 °C
Correa que puede resistir temperaturas máximas de hasta 371 °C
Cinghie possono resistere alle temperature di massimo 371°C
Gurt hitzeresistent bis maximal 371°C



Sangle pouvant résister à des projections de métal en fusion
Strap that can withstand splashes of molten metal
Correa que puede resistir proyecciones de metal en fusión
Cinghie possono resistere alle proiezioni di metallo in fusione
Gurt beständig gegen Spritzer von Schmelzmetall