



Length :	CE	Weight:
20 m		7.95 kg

KRATOS SAFETY

689 Chemin du Buclay
38540 Heyrieux – FRANCE

Tel : +33 (0)4 72 48 78 27

Fax : +33 (0)4 72 48 58 32

www.kratossafety.com / info@kratossafety.com

- To be used for raising or lowering persons or material into confined spaces.
- Equipped with bolting fixture for robust fitting on the Tripod (FA 60 001 00 / FA 60 002 00 / FA 60 101 00 / FA 60 102 00).
- Can also be mounted on our MultiSafeWay (FA 60 022 00).
- To be used with a retractable fall arrester (EN360) when deployed for raising or lowering a person.
- Length of wire rope: 20 m.
- Galvanized steel cable diam.: 4.8 mm.
- Has a support handle.
- 1 steel screw-locking karabiner, opening 18 mm, ref. FA 50 101 17.

Compliance: EN 1496:2006 (Class A), Machinery Directive 2006/42/CE, EN 13157:2004, Directive ATEX 2014/34/UE (Ex II 2 G Exh IIC T6 Gb).

Specifications:

- **Safe working load** (for a person) as per EN1496: 135 kg.
- **Max. working load** (for a load) as per Machinery Directive: 250 kgs.

Material of components:

Wire rope: Galvanized steel

Connector: Steel

HS CODE

84251920

CARTON SIZE / PCS.

40 x 30 x 19 cm / 1

Extension from the original report SPC0256516/1716
Issue 2 Extension 1 dated 21/12/2018

Satra Technology Centre, N°0321

Wyndham Way, Telford Way, Kettering
Northamptonshire, NN16 8SD, United Kingdom

ACKNOWLEDGEMENT OF RECEIPT N°3975/1/2018 (ATEX)**Technická Inšpekcia, a.s. N°1354**

Trnavská cesta 56, 821 01 Bratislava, Slovenská Republika