



TECHNICAL SHEET

FA 30 305 15



Designation: FIRE FREE Energy Absorbing Webbing Lanyard

Designed to offer a perfect solution for workers doing welding at height. We recommend its use for: shipbuilding, building steelwork, ...

- Energy absorber in 44mm wide webbing which reduces the impact of the fall less than 6 KN
- Aramid webbing lanyard width 45 mm
- Energy Absorber covered by a non fire fabric.

Connectors:

1 steel scaffold hook, opening 55 mm, ref. FA5020755 and 1 steel screw-locking karabiner, opening 17 mm, ref. FA5010117

Compliance:

EN355 : 2002 and tested as per VG11 - 89/686/CEE, ISO9150 : 1988 and ISO15025 : 2005

Length: 1.5 m (connectors included)


Also exists in 1 m and 2 m

Materials:

Lanyard: aramid

Absorber: polyester and polyamide

Connectors: steel



HS code

56090090

Carton Size / Pieces

60x40x24 /20

Unit Weight

1.14 Kg

AET: N° 4301 Issue 6 Extension 2

Satra Technology Centre, N°0321
Wyndham Way, Telford Way, Kettering,
Northamptonshire, NN16 8SD, United Kingdom.

Article 11: GB07/73551

SGS United Kingdom Ltd., N° 0120
Unit 202B, Worle Parkway,
Weston-super-Mare, BS22 6WA, United Kingdom



Maj. : 07/14

ZI les portes du Dauphiné

4 rue de l'Aigue

69 780 St Pierre de Chandieu – France

Tel : +33 (0)4 72 48 78 27 Fax : + 33 (0)4 72 48 58 32

www.kratossafety.com info@kratossafety.com

