



TECHNICAL SHEET FA 30 403 15

FORKED ENERGY ABSORBING WEBBING LANYARD



Forked Energy Absorbing Webbing Lanyard

- 44 mm wide webbing Energy Absorber, which reduces the impact of the fall less than 6 KN.
- Lanyard in polyester webbing, width 44 mm.

Connectors:

2 aluminum scaffold hooks double action, opening 60 mm, ref. FA 50 208 60 and 1 aluminum screw-locking karabiner, opening 22 mm, ref. FA 50 103 22.

Compliance:

EN355:2002 and tested according VG11 requirements - 89/686/CEE EN1149-1:2006 (surface resistivity) and ATEX Directive 94/9/CE, EN13463-1 (2001) and EN136463-5 (2006).

Material of components:

Lanyard: polyester with antistatic properties.
Absorber: polyamide and polyester with antistatic properties.
Connectors and buckles: aluminium.

Size:	CE	Weight:
1.5 mtr (connectors included)		1.47 kg

KRATOS SAFETY

689 Chemin du Buclay
38540 Heyrieux – FRANCE

Tel : +33 (0)4 72 48 78 27
Fax : +33 (0)4 72 48 58 32

www.kratossafety.com / info@kratossafety.com

HS CODE
56090090
CARTON SIZE / PCS.
80 x 40 x 24 / 10
AET N°4304 I6 E1
Satra Technology Centre, N°0321 Wyndham Way, Telford Way, Kettering Northamptonshire, NN16 8SD, United Kingdom
ARTICLE 11 GB07/73551
SGS United Kingdom Ltd., N°0120 Unit 202B, Worle Parkway, Weston-super-Mare, BS22 6WA, United Kingdom