



TECHNICAL SHEET FA 30 405 15

FORKED DIELECTRIC ENERGY ABSORBING WEBBING LANYARD, LG. 1.50 M



Dielectric webbing lanyard with an energy absorber, designed to protect operators working in an environment with potential dielectric hazards.

- Energy absorber in 44 mm wide webbing, which reduces the impact of the fall to less than 6kN.
Energy absorber with a fall indicator:



Black sleeve for increased longevity and UV-resistance.

- 30 mm wide polyester webbing.

Connectors: 1 dielectric snap hook, gate opening 15 mm, FA 50 223 15 at the absorber end, and 2 dielectric rebar hooks, gate opening 55 mm, FA 50 222 55, at the other end.

Compliance : EN355:2002.

Material of components:

Webbing: Polyester

Absorber: Polyester and Polyamide

Connectors: Steel with insulating polymer composite that can withstand a maximal voltage of 14 kV.

Length:	CE	Weight:
1.50 m		2.03 kg

KRATOS SAFETY

689 Chemin du Buclay,
38540 Heyrieux – FRANCE

Tel. : +33 (0)4 72 48 78 27
Fax : +33 (0)4 72 48 58 32

www.kratossafety.com / info@kratossafety.com

HS CODE
5609 00 90
CARTON SIZE / PIECES
80 x 40 x 24 cm / 10
AET N°4304 I8 E
Satra Technology Centre, N°0321 Wyndham Way, Telford Way, Kettering Northamptonshire, NN16 8SD, United Kingdom
ARTICLE 11 GB07/73551
SGS United Kingdom Ltd., N°0120 Unit 202B, Worle Parkway, Weston-super-Mare, BS22 6WA, United Kingdom