



TECHNICAL SHEET FA 30 722 20

Expandable energy absorbing lanyard, max. lg. 1.80 m



Expandable energy absorbing lanyard, made up of:

- Energy absorber in 45 mm wide controlled-tear webbing, which reduces the impact of the fall to less than 6 kN,
- 35 mm wide Polyester expandable/elasticated webbing lanyard.
- Loops protected by an abrasion resistant tubular webbing.
- Compact energy absorber, protected by a small zipper pouch, easily openable for internal control of the energy absorber webbing.
- Connectors: One green aluminium scaffold hook, gate opening 60 mm, FA 50 208 60.
- **Max. user weight:** 140 kg.

Compliance: EN355:2002

- **Expanded length:** 1.80 m
- **Relaxed length:** approx. 1.40 m

Material of components:

Webbing: Polyester

Connector: Aluminium

Length:	CE	Weight:
Max. 1.80 m		0.99 kg

KRATOS SAFETY

689 Chemin du Buclay
38540 Heyrieux – FRANCE

Tel : +33 (0)4 72 48 78 27
Fax : +33 (0)4 72 48 58 32

www.kratossafety.com / info@kratossafety.com

HS CODE

56090090

CARTON SIZE / PCS.

80 x 40 x 24 / 10

AET N° I E

Satra Technology Centre, N°0321
Wyndham Way, Telford Way, Kettering
Northamptonshire, NN16 8SD, United Kingdom

ARTICLE 11 GB07/73551

SGS United Kingdom Ltd., N°0120
Unit 202B, Worle Parkway,
Weston-super-Mare, BS22 6WA, United Kingdom