



TECHNICAL SHEET FA 40 502 15

RESTRAINT KERNMANTLE ROPE LANYARD



Restraint Kernmantle Rope Lanyard

- Made up of 12mm diam polyamide kernmantle rope.
- Abrasion resistant thimble to protect the loops from being damaged by metallic contact.
- Sewing protected with a strong transparent covering sleeve which protects the ends and also make stitches visible for easy inspection before the use.
- Breaking strength : 22 kN

Connector : 1 steel scaffold hook, opening 55 mm, ref. FA5020755

Compliance : EN354 : 2002

Material of components:

Lanyard: polyamide

Connector : steel

Size:		Weight:
1.5 mtr		0.68 kg

KRATOS SAFETY

689 Chemin du Buclay
38540 Heyrieux – FRANCE

Tel : +33 (0)4 72 48 78 27

Fax : +33 (0)4 72 48 58 32

www.kratossafety.com / info@kratossafety.com

HS CODE

56075090

CARTON SIZE / PCS.

60 x 40 x 24 / 25

AET N°2577 I2 E4

Satra Technology Centre, N°0321
Wyndham Way, Telford Way, Kettering
Northamptonshire, NN16 8SD, United Kingdom

ARTICLE 11 GB07/73551

SGS United Kingdom Ltd., N°0120
Unit 202B, Worle Parkway,
Weston-super-Mare, BS22 6WA, United Kingdom