








HS CODE
56090090
CARTON SIZE / PCS.
60 x 40 x 36 / 25
AET N° 2777/10965-01/E01-01
Satra Technology Europe Ltd., N° 2777, Bracetown Business Park, Clonee, Dublin, D15YN2P, Ireland
MODULE D FI14/14003.02
SGS Fimko Oy, N°0598 Takomotie 8, 00380 HELSINKI, Finland



REF.	FA 30 300 15	FA 30 300 20
 <p>LG. KG</p>	1.5 m (connector included)	1.8 m (connector included)
	EN 355:2002	
MAT.	 30 mm Polyester	
	35 mm	
	---	
	NO	
+	---	
	0.39 KG	0.42 KG



Largeur de l'absorbeur d'énergie
Width of the energy absorber
Ancho del absorbedor de energía
Larghezza del assorbitore di energia
Breite des Falldämpfers



Longueur Poids maxi utilisateur
Length Max. user weight
Longitud Peso máximo del usuario
Lunghezza Peso Max. dell'utente
Länge Höchstgewicht des Benutzers



Matière connecteur haut / connecteur bas
Material of top connector / bottom connector
Material conector alto / conector bajo
Materiale connettore alto / connettore basso
Material oberes / unteres Verbindungselement



Ouverture
Gate opening
Apertura
Apertura
Öffnung



Homologué pour le travail à proximité d'arêtes vives
Approved for work near sharp edges
Homologado para trabajo cerca de aristas vivas
Omologato per lavoro in prossimità di spigoli vivi
Zugelassen für Arbeiten in der Nähe scharfer Kanten