



TECHNICAL SHEET

FA 10 211 00



Designation : Harness with belt FIRE FREE

This harness has been designed to offer a perfect solution for workers doing welding at height. We recommend its use for : shipbuilding, building steelwork, ...

Attachment Elements : 1 Dorsal D-Ring (A) ●, 1 sternal attachment (A/2) ● with 2 textile loops for fall arrest and 2 lateral D-Rings ● at waist level for work positioning.

Adaptability : Adjustable shoulder, thigh straps and waist belt.

Convenience : Static strength of the harness webbing has been tested after being exposed to the small molten metal splashes. Automatic buckles on thigh straps and on the belt.

Compliance : Complies to the standards EN 361:2002, EN 358 :2000, ISO 9150: 1988 and ISO 15025: 2005



Size : S - XL

Materials :

Straps : aramid
Buckles : steel



HS code

63072090

Carton Size/ Pieces

60x40x24 / 5

Unit Weight

2.55 Kg

AET: N° xxxx Issue Extension

Satra Technology Centre, N°0321
Wyndham Way, Telford Way, Kettering,
Northamptonshire, NN16 8SD, United Kingdom.

Article 11: GB07/73551

SGS United Kingdom Ltd., N° 0120
Unit 202B, Worle Parkway,
Weston-super-Mare, BS22 6WA, United Kingdom



Maj. : 07/2013

ZI les portes du Dauphiné

4 rue de l'Aigue

69 780 St Pierre de Chandieu – France

Tel : +33 (0)4 72 48 78 27 Fax : + 33 (0)4 72 48 58 32

www.kratossafety.com info@kratossafety.com

