

FILTER

Model: 200 A2**P/N 124200000**

Gas filter with standard thread connector to **EN 148-1** for organic vapours having boiling point higher than 65°C. The filter can be used with full face masks type **TR 82**, **TR 2002 CL2** and **TR 2002 CL3** and halfmasks **ST 85** or equivalent, provided that they are fitted with EN 148-1 connector.



TECHNICAL DATA

Breathing resistance

at 30 l/min: 1.0 mbar

at 95 l/min: 3.7 mbar

Duration at gases

Filter type	Class	Testing Gas	Testing Concentration (PPM)	Testing Flow (l/min)	Testing HR (%)	Breakthrough concentration (PPM)	Duration Required (min)	Duration Tested (min)
A	2	C ₆ H ₁₂	5000	30	70	10	35	60

Limitations for use

Do not use in areas where the oxygen concentration is lower than 17% in volume nor in presence of gases different from those clearly indicated, dusts, fumes and mists.

CLASSIFICATION

Filter complying with the provisions of Regulation (EU) **2016/425**.**Gas Filter, class 2, to EN 14387:2004 + A1:2008.**

Label colour code: brown

MARKING





FILTER

Model: 200 A2
P/N 124200000

MATERIALS

Housing: polypropylene
Filter Media: activated carbon

STORAGE

Store at temperatures between -20 and +50 °C and RH <80%

WEIGHT

190 g approximately

DIMENSIONS/PACKING

The filter is sold in 4 piece boxes with dimensions 220 x 220 x 90 mm

SHELF LIFE

Filters duly stored and in their original packaging will last five years from production. The expiry date is stamped onto the filter label and its packaging.

For more information please check the notes along with the products or the ones published on the website: www.spasciani.com

NOTE: SPASCIANI SpA does not take any responsibility for any possible and unintentional mistake and reserve the faculty of modify materials and technical characteristics of its products at any time and without any notice. The pictures are purely indicative and may not represent the actual product described in the text.