



## TECHNICAL SHEET FA 20 100 10

ANCHOR LINE FOR FALL ARRESTER FA 20 100 00 A OR B



Anchor line for fall arrester FA 20 100 00 A or B

- Made up of 14-16 mm diameter polyamide twisted rope.
- Abrasion resistant thimble to protect the loops from being damaged by contact with metal parts.
- Spliced end protected with a strong transparent covering sleeve.
- Colored tracer strand losing colour to show that the lanyard is unfit for use.

Compliance: Conforms to EN 353-2: 2002.

**Minimum breaking strength of the twisted rope:** 29 kN.

### Material of components:

Rope: Polyamide

Size:	<b>CE</b>	Weight:
10 mtrs Also exists in 20, 30, 40, 50, 100, 200 mtrs. Other length on request.		1.25 kg

### KRATOS SAFETY

689 Chemin du Buclay  
38540 Heyrieux – FRANCE

Tel : +33 (0)4 72 48 78 27

Fax : +33 (0)4 72 48 58 32

[www.kratossafety.com](http://www.kratossafety.com) / [info@kratossafety.com](mailto:info@kratossafety.com)

### HS CODE

56090090

### CARTON SIZE / PCS.

80 x 40 x 24 / 10

### AET N°2664 I3 E3

Satra Technology Centre, N°0321  
Wyndham Way, Telford Way, Kettering  
Northamptonshire, NN16 8SD, United Kingdom

### ARTICLE 11 GB07/73551

SGS United Kingdom Ltd., N°0120  
Unit 202B, Worle Parkway,  
Weston-super-Mare, BS22 6WA, United Kingdom