



TECHNICAL SHEET FA 20 100 20

ANCHOR LINE FOR FALL ARRESTER FA 20 100 00 A OR B



Anchor line for fall arrester FA 20 100 00 A or B

- Made up of 14-16 mm diameter polyamide twisted rope.
- Abrasion resistant thimble to protect the loops from being damaged by contact with metal parts.
- Spliced end protected with a strong transparent covering sleeve.
- Colored tracer strand that loses colour to show that the lanyard is unfit for use.

Compliance: Conforms to EN 353-2 : 2002.

Minimum breaking strength of the twisted rope: 29 kN.

Material of components:

Rope: Polyamide

Size:	CE	Weight:
20 mtrs Also exists in 10, 30, 40, 50, 100, 200 mtrs. Other length on request.		2.50 kg

KRATOS SAFETY

689 Chemin du Buclay
38540 Heyrieux – FRANCE

Tel : +33 (0)4 72 48 78 27
Fax : +33 (0)4 72 48 58 32

www.kratossafety.com / info@kratossafety.com

HS CODE
56090090
CARTON SIZE / PCS.
60 x 40 x 24 / 05
AET N°2664 I3 E3
Satra Technology Centre, N°0321 Wyndham Way, Telford Way, Kettering Northamptonshire, NN16 8SD, United Kingdom
ARTICLE 11 GB07/73551
SGS United Kingdom Ltd., N°0120 Unit 202B, Worle Parkway, Weston-super-Mare, BS22 6WA, United Kingdom