




## TECHNICAL SHEET FA 30 305 10

### FIRE FREE ENERGY ABSORBING WEBBING LANYARD



Designed to offer a perfect solution for workers doing welding at height. We recommend its use for: shipbuilding, building steelwork, ...

- Energy absorber in 44mm wide webbing which reduces the impact of the fall to less than 6 KN.
- Aramid webbing lanyard width 45 mm.
- Energy Absorber covered by a non fire fabric.

**Connectors:** 1 steel scaffold hook, opening 55 mm, ref. FA 50 207 55 and 1 steel screw-locking karabiner, opening 17 mm, ref. FA 50 101 17.

**Compliance:** EN355 : 2002 and tested as per VG11 - 89/686/CEE, ISO9150 : 1988 and ISO15025 : 2005.

#### Material of components:

Lanyard: aramid  
Absorber: polyester and polyamide  
Connectors: steel

<b>Size:</b> 1 mtr (connector included) Also exists in 1.5 and 2 mtr	<b>CE</b>	<b>Weight:</b>  1.08 kg
--	-----------	-------------------------------

#### **KRATOS SAFETY**

689 Chemin du Buclay  
38540 Heyrieux – FRANCE

Tel : +33 (0)4 72 48 78 27  
Fax : +33 (0)4 72 48 58 32

[www.kratossafety.com](http://www.kratossafety.com) / [info@kratossafety.com](mailto:info@kratossafety.com)

<b>HS CODE</b> 56090090
<b>CARTON SIZE / PCS.</b> 60 x 40 x 24 / 10
<b>AET N°4301 I6 E2</b>
Satra Technology Centre, N°0321 Wyndham Way, Telford Way, Kettering Northamptonshire, NN16 8SD, United Kingdom
<b>ARTICLE 11 GB07/73551</b>
SGS United Kingdom Ltd., N°0120 Unit 202B, Worle Parkway, Weston-super-Mare, BS22 6WA, United Kingdom