

FILTER

Model: 205 A2B2E2K1 P3 R D
P/N 124720000

Combined filter with standard thread connector to **EN 148-1** protecting against gases of the ABEK type, dusts, fumes and mists.

The filter can be used with masks type **TR 82**, **TR 2002 CL2** and **TR 2002 CL3** or equivalent, provided that they are fitted with EN 148-1 connector.

TECHNICAL DATA

Breathing resistance

at 30 l/min: 2.1 mbar

at 95 l/min: 8.2 mbar



Duration at gases

Filter type	Class	Testing Gas	Testing Concentration (PPM)	Testing Flow (l/min)	Testing HR (%)	Breakthrough concentration (PPM)	Duration Required (min)	Duration Tested (min)
A	2	C6H12	5000	30	70	10	35	>45
B	2	Cl2	5000	30	70	0.5	20	26
		H2S	5000	30	70	10	40	>50
		HCN	5000	30	70	10	25	35
E	2	SO2	5000	30	70	5	20	24
K	1	NH3	1000	30	70	25	40	55

Tests performed against special gasses:

- **Formaldehyde (HCHO)**, **Nitrogen Dioxide (NO₂)**, **Phosphine (PH₃)** to **NIOSH-CBRN** requirements

Test Conditions	Con.Test	Air Flow l/min	Air Humidity %	Breakthrough Conc. (ppm)	Breakthrough Time
Formaldehyde - HCHO	300	64	25+/-5	1	96
		64	80+/-5		84
		100	50+/-5		>15
Nitrogen Dioxide - NO ₂	200	64	25+/-5	1 NO ₂	19*
		64	80+/-5	o	28*
		100	50+/-5	25 NO	13*
Phosphine - PH ₃	300	64	25+/-5	0.3	132
		64	80+/-5		234
		100	50+/-5		>15

*breakthrough to NO

FILTER

Model: 205 A2B2E2K1 P3 R D

P/N 124720000

Performance particle filtration

Filter type	Penetration (l/min)	Test Aerosol	Penetration Max Allowed (%)	Test 1 (%)	Test 2 (%)	Test 3 (%)
P R	95	NaCl	0.05	0.002	0.002	0.0007
		Paraffin oil	0.05	0.007	0.0008	0.0009

Test Filter Type :

Test 1: Penetration (media calculated 30 sec after the test beginning)

Test 2: Max Penetration till 120 mg aerosol exposition

Test 3: Penetration (media calculated 30 sec after the test beginning) after 120 mg aerosol exposition and 24h storage.

"D" clogging test with Dolomite Dust.

Filter is submitted to a clogging test with a concentration of Dolomite of 263 mg.h.m³.

Inhalation resistance: a 95 l/min: 8.4 mbar (request < 10.5 bar)

Filter type	Test Flow	Test Aerosol	Penetration Max Allowed (%)	Penetration Max Measured (%)
P R	95	NaCl	0.05	0.0007
		Paraffin oil	0.05	0.0008

Marking D means the filter passed the clogging test with Dolomite dust and it has high performance in dusty and sandy settings.

Limitations for use

Do not use in areas where the oxygen concentration is lower than 17% in volume nor in presence of gases different from those clearly indicated.

CLASSIFICATION

Filter complying with the provisions of Regulation (EU) **2016/425 (PPE)**

The filter is certified:

1 EN 14387:2004 + A1:2008 for types ABEK (class 2), NO and Hg

2 EN143:2000 / A1:2006 for the particle filter media (class **P3 R D**)

Label colour code: brown, grey, yellow, green, white

MARKING



For more information please check the notes along with the products or the ones published on the website: www.spasciani.com

NOTE: SPASCIANI SpA does not take any responsibility for any possible and unintentional mistake and reserve the faculty of modify materials and technical characteristics of its products at any time and without any notice. The pictures are purely indicative and may not represent the actual product described in the text.



FILTER

Model: 205 A2B2E2K1 P3 R D
P/N 124720000

MATERIALS

Housing: polypropylene

Filter Media: activated carbon and filter paper

STORAGE

Store at temperatures between -20 and +50°C and RH <80%

WEIGHT

265 g approximately

DIMENSIONS/PACKING

The filter is sold in 1 piece boxes with dimensions 105 x 105 x 110 mm

SHELF LIFE

Filters duly stored and in their original packaging will last five years from production. The expiry date is stamped onto the filter label and its packaging.

For more information please check the notes along with the products or the ones published on the website: www.spasciani.com

NOTE: SPASCIANI SpA does not take any responsibility for any possible and unintentional mistake and reserve the faculty of modify materials and technical characteristics of its products at any time and without any notice. The pictures are purely indicative and may not represent the actual product described in the text.